

DMM 902, DMM 903 & DMM 904 Pocket Size Multimeters

Despite their small format, these instruments have a very high safety approval (CAT IV 600v, CAT III 1000v). They are protected against overloading by an electronic fuse. When not in use, the test probes can be parked at the rear of the instrument body.

Features:

- LCD display with backlight
- Built-in, non-contact AC voltage detector plus flashlight
- Measures voltage, resistance, diode function & continuity
- Double-moulded case
- CAT III 1000v, CAT IV 600
- Auto-ranging with auto power off
- Silicone test leads
- Protective holster



Specifications:

Model	DMM 902	DMM 903	DMM 904
Display	2000-count	2000-count	4000-count
DC Voltage Ranges	0.1mv ~ 600v		
AC Voltage Ranges	1mv ~ 600v		
DC Current	-	0.1µA ~ 200mA	0.1µA ~ 200mA
AC Current	-	0.1µA ~ 200mA	0.1µA ~ 200mA
Resistance	0.1Ω ~ 20mΩ	0.1Ω ~ 20mΩ	0.1Ω ~ 40mΩ
Capacitance	-	-	1pF ~ 200µF
Frequency	-	-	0.001Hz ~ 10KHz
Symmetry	-	-	0.5 ~ 99%
Auto Range Selection	Yes		
AC Measurement	Average		
Diode Test	Yes		
Continuity Test	Yes		
Auto Power Off	Yes		
Data Hold	Yes	Yes	-
Record Function	Max Hold	Max Hold	-
AC Measurement Bandwidth	40Hz ~ 500Hz		
Low Battery Indication	Yes		
Measuring Rate	2 per second		
Dimension	104(H) x 54(W) x 36(D) mm		
Weight	145g		
Power Supply	2 x AAA 1.5v batteries (inc)		
Standard Accessories	Holster, Manual, Batteries		
Approvals	CAT III 1000v, CAT IV 600v		
Temperature Limits	Operating 0 ~ 40°C, RH < 80% non condensed		
Storage	-10 ~ 50°C, RH < 70% non condensed		
Safety Standards	EN 61010-1, CE, Pollution Degree II		